

Technical specifications

Model	centormail 240 plus	centormail 240 dynamic	centormail 300 plus	centormail 300 dynamic	
Standard features & functions					
Letter catch tray	yes	yes	yes	yes	
Mixed mail feeder	yes	yes	yes	yes	
Letter thickness	up to 20mm	up to 20mm	up to 20mm	up to 20mm	
Sealer and power sealer	optional	optional	optional	optional	
Dynamic scale	upgrade option	yes	upgrade option	yes	
Static scale	yes (5kg)	yes (5kg)	yes (5kg)	yes (5kg)	
Letters per minute	120	120	150	150	
Letters per minute - dynamic weigh	n/a	60	n/a	60	
Differential weighing	yes	yes	yes	yes	
Label dispenser	yes	yes	yes	yes	
Integrated modem	yes	yes	yes	yes	
Chip card reader	yes	yes	yes	yes	
Master cards	yes	yes	yes	yes	
User cards	optional	optional	optional	optional	
Accounts	100 upgradeable to 300	100 upgradeable to 300	300	300	
Accounts output to PC using infoprint	optional	optional	optional	optional	
Adverts	up to 15	up to 15	up to 15	up to 15	
SMS text logos	up to 8	up to 8	up to 8	up to 8	
Incoming mail stamp	yes	yes	yes	yes	
High postage warning	yes	yes	yes	yes	
Low postage warning	yes	yes	yes	yes	
Serial interface	2	2	2	2	
Ink system	2 ink cartridges	2 ink cartridges	bulk ink supply	bulk ink supply	
Second carrier (DX)	optional	optional	optional	optional	
PPI facility	optional	optional	optional	optional	
Standard Specifications	Postage meter and base	Dynamic scale	Feeder	Sealer	Power sealer
Width	550mm (meter) 200mm (hand feed tray) 302-415mm (catch tray)	550mm	550mm	305mm	103mm
Depth	540mm	315mm	315mm	315mm	245mm
Height	340mm	340mm	290mm	290mm	340mm
Weight	25kg	13.5kg	12.5kg	7.5kg	2.7kg
Power	240V, 50Hz 1.0A	240V, 50Hz	240V	240Vdc, 2A	240Vdc, 2A
Weighing range	static scale: 0-5kg	0-1kg	N/A	N/A	N/A
Power consumption	115W	185W	225W	260W	300W
Display	LCD, 320x240 pixel with LED illumination				
Print system	ink-jet printing featuring HP technology				
Print area	185mm x 25mm				
Print resolution	300DPI				
Operating conditions	59°F to 95°F / +15°C to +35°C for indoor use only, do not expose to direct sunlight, relative humidity 20% to 70% non-condensing				
Storage conditions	59°F to 95°F / +15°C to +35°C relative humidity 5% to 80%, non-condensing				
Noise emission	<67db (A) (normal operation) <45db (A) (stand-by)				

Specifications subject to change.

Your mail is our strength

Francotyp-Postalia Ltd.
Lakeside House,
74 Questor,
Powdermill Lane,
Dartford,
Kent DA1 1EF
FREEPHONE 0500 223563

Internet: www.fpmailing.co.uk

Inkjet
Technology by



Versatile and powerful . . .



The innovative mixed mail
franking system
with inkjet technology

centormail 240 Plus
240 Dynamic
300 Plus
300 Dynamic

centormail – totally versatile

centormail



the modular, mixed mail,
exclusive vertical feeding system from FP

centormail Modular Design

The most innovative and efficient postage mailing system of its kind.

The centormail system is totally modular. Components like the automatic feeder, dynamic scales and infoprint software can be added as your needs grow.

Loading postage is simple. centormail has an internal modem which connects to the FP-Teleset service to load postage at the touch of a button.

Infoprint - a unique way of capturing accounting data and displaying it on your PC. Infoprint also allows you to export your accounting data into Microsoft Excel for further manipulation.

The centormail Card System

Only people provided with a coded centormail card are authorised to use centormail - it is locked for unauthorised persons. Up to 300 departmental accounts can be equipped with centormail cards. When the postal service changes its rates, simply insert a new card loaded with the new rates and centormail does the rest.

- Real mixed mail feeding
- Unique vertical feeding system
- Smudge-free digital inkjet printing
- Super quiet feeder
- centormail security card
- Advertising blocks on centormail card
- Handles items up to 20mm thick
- Handles Jiffy bags, catalogues and bulky mailings
- Internal modem
- Integrated accounting with infoprint

Ink-jet printing

The fully electronic print head never touches the envelope surface delivering clean crisp franks that dry on contact, this makes centormail quiet enough for every office.

The cliché can be changed at the touch of a button, what's more you can have up to 9 advertising slogans and 9 types of mail clichés with more on the centormail card.



centormail offers security and flexibility.



Dynamic Scales

The centormail Dynamic Scales weigh every piece of unsorted mail automatically, calculating the correct postage “on the move” and transmitting the weight to the postage meter which calculates the correct postage and immediately franks the envelope. Items up to 20mm thick and 1kg, including Jiffy bags, can be loaded without interrupting the franking operation.

Whisper Quiet Operation

centormail feeds letters vertically like large mail sorting machines, now you can have genuine ‘mixed mail’ feeding plus reloading without interruption. Incredibly quiet, less than 60dB(A). German engineered to work quietly anywhere in your office.

User Friendly Control Panel and Display

The multi-purpose display makes centormail one of the easiest postage meters in the world to use with step-by-step screen prompts, error messages and account functions.

- Automatically stores frequently used time, date and postage settings

Enhance your company's image

- with SMS tailored messages
- 15 personalised logos



Label Dispenser

For larger packages, simply enter the number of labels you need printed and press the label key. centormail automatically feeds and prints the quantity of labels.



With integrated scale and automatic feeder

Integrated Static Scales

The integrated scale allows you to select the class of service and then automatically sets the postage rate. It can be used for items up to 5kg and/or has a separate platform up to 30kg.



With integrated, dynamic scale and automatic feeder